



*Quality Products. Service Excellence.*

## Type 4X Stainless Steel Freestanding Enclosure *HN4 FS SS Series*

Continuous Hinge Door with Handle



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls with provision for panel mounting or rack mounting of equipment.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.
- A variety of inner panels, rack mounting rails and swing out frames are available to provide flexibility in mounting arrangements.

### Construction

- Formed 12 gauge 304 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Mounting channels are welded on the inside of the enclosure for mounting of optional inner panels or rack equipment rails.

### Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 3
  - IEC 60529, IP66

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Optional inner panels are finished in white powder paint.

### Accessories

- |                    |                             |
|--------------------|-----------------------------|
| • Inner Panels     | • Panel Rails               |
| • Swing Out Frames | • Door Stop Kit             |
| • Drip Shield Kit  | • Type 12/4, 4X Handle Kits |
| • Window Kits      | • Climate Control           |
| • Lighting         | • General Accessories       |

# New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

## Single Access

304 S.S.	316 S.S.	Enclosure			Optional Full Size
Part No.	Part No.	H	W	D	Panel
<a href="#">HN4FS602418SS</a>	<a href="#">HN4FS602418S16</a>	60.06	24.06	18.06	<a href="#">60TWFW</a>
<a href="#">HN4FS722418SS</a>	<a href="#">HN4FS722418S16</a>	72.06	24.06	18.06	<a href="#">72WFW</a>
<a href="#">HN4FS723018SS</a>	<a href="#">HN4FS723018S16</a>	72.06	30.06	18.06	<a href="#">72XFW</a>
<a href="#">HN4FS723618SS</a>	<a href="#">HN4FS723618S16</a>	72.06	36.06	18.06	<a href="#">72YFW</a>
<a href="#">HN4FS902420SS</a>	<a href="#">HN4FS902420S16</a>	90.06	24.06	20.06	<a href="#">90YFW</a>
<a href="#">HN4FS903620SS</a>	<a href="#">HN4FS903620S16</a>	90.06	36.06	20.06	<a href="#">90YFW</a>
<a href="#">HN4FS603624SS</a>	<a href="#">HN4FS603624S16</a>	60.06	36.06	24.06	<a href="#">60TYFW</a>
<a href="#">HN4FS722424SS</a>	<a href="#">HN4FS722424S16</a>	72.06	24.06	24.06	<a href="#">72WFW</a>
<a href="#">HN4FS723024SS</a>	<a href="#">HN4FS723024S16</a>	72.06	30.06	24.06	<a href="#">72XFW</a>
<a href="#">HN4FS723624SS</a>	<a href="#">HN4FS723624S16</a>	72.06	36.06	24.06	<a href="#">72YFW</a>
<a href="#">HN4FS903624SS</a>	<a href="#">HN4FS903624S16</a>	90.06	36.06	24.06	<a href="#">90YFW</a>
<a href="#">HN4FS723630SS</a>	<a href="#">HN4FS723630S16</a>	72.06	36.06	30.06	<a href="#">72YFW</a>
<a href="#">HN4FS723636SS</a>	<a href="#">HN4FS723636S16</a>	72.06	36.06	36.06	<a href="#">72YFW</a>
<a href="#">HN4FS903636SS</a>	<a href="#">HN4FS903636S16</a>	90.06	36.06	36.06	<a href="#">90YFW</a>

Alternative inner panel options also available.

## Dual Access

304 S.S.	316 S.S.	Enclosure			Optional Full Size
Part No.	Part No.	H	W	D	Inner Panel
<a href="#">HN4FS722424DASS</a>	<a href="#">HN4FS722424DS16</a>	72.06	24.06	24.06	<a href="#">72WFW</a>
<a href="#">HN4FS723024DASS</a>	<a href="#">HN4FS723024DS16</a>	72.06	30.06	24.06	<a href="#">72XFW</a>
<a href="#">HN4FS723624DASS</a>	<a href="#">HN4FS723624DS16</a>	72.06	36.06	24.06	<a href="#">72YFW</a>
<a href="#">HN4FS903624DASS</a>	<a href="#">HN4FS903624DS16</a>	90.06	36.06	24.06	<a href="#">90YFW</a>
<a href="#">HN4FS722430DASS</a>	<a href="#">HN4FS722430DS16</a>	72.06	24.06	30.06	<a href="#">72WFW</a>
<a href="#">HN4FS722436DASS</a>	<a href="#">HN4FS722436DS16</a>	72.06	24.06	36.06	<a href="#">72WFW</a>
<a href="#">HN4FS723636DASS</a>	<a href="#">HN4FS723636DS16</a>	72.06	36.06	36.06	<a href="#">72YFW</a>
<a href="#">HN4FS903636DASS</a>	<a href="#">HN4FS903636DS16</a>	90.06	36.06	36.06	<a href="#">90YFW</a>

Alternative inner panel options also available.

*Data subject to change without notice*