



*Quality Products. Service Excellence.*

## Type 1 Mild Steel Splitter Box *CSB Series*

Hinged Door with Screw



### Application

- The splitter boxes are designed for indoor distribution of up to 600 A (max) service using either 3 or 4 wires. 75° C conductor ampacity permitted.

### Standards

- CSA Type 1
- Complies with
  - IEC 60529, IP20

### Construction

- Formed and spot welded from 14 or 16 gauge steel.
- Factory installed splitter blocks - 3 or 4 wire option. Empty box without splitter blocks also offered.
- Series of knockouts on each side.
- Padlocking hasp.

### Finish

- Enclosure and cover are finished in ANSI 61 gray powder coating.

### Accessories

- Splitter Blocks
- Grounding Kits

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

3 Wire	4 Wire	Less Blocks	CU/AL	Enclosure		
Part No.	Part No.	Part No.	Amps	H	W	D
CSB73	CSB74	CSB70	70/70	12.00	10.00	4.00
CSB103	CSB104	CSB100	125/120	15.00	10.00	4.00
CSB203	CSB204	CSB200	225/180	18.00	12.00	5.00
CSB403	CSB404	CSB400	400/400	24.00	17.00	6.00
CSB603*	CSB604*	CSB600*	600/600	30.00	24.00	7.00

\* 14 gauge steel

*Data subject to change without notice*