



Quality Products. Service Excellence.

## Rack Mount Intake Blowers *HB Series*

### Features



- Standard 19" rack mount
- Air delivery from more than 50% of their 17" width
- Internal neoprene isolation mounts reduce transmission of vibration to the rack
- Air intake only, to pressurize the rack with filtered air
- Heavy steel construction
- Attractive 19" stainless steel grille included
- 115 VAC, 50/60 Hz. motor is UL recognized, CSA certified, ball bearing type, cooled by incoming air
- Includes permanent filter (replacement filters available below)
- Comes with 6' STJ 3- wire cord
- Optional replacement filters come in a pack of five (5).



### Accessories



- Filter Coat

- Mounting Hardware



|          | Free Flow Air  | Running | RPM         | Noise | Blower             | Ambient         | Mounting Dimentions |        | Replacement   |
|----------|----------------|---------|-------------|-------|--------------------|-----------------|---------------------|--------|---------------|
| Part No. | Delivery (CFM) | Amps    | Nominal     | (dB)  | Type               | Temperature (F) | Rack Units          | Height | Filter 5-Pack |
| HB2160A  | 145 / 125      | 0.7     | 2500 / 3000 | 62    | TransverseFlow     | -20 to +250     | 2U                  | 3.50   | HB2UFILTER    |
| HB3250A  | 155 / 200      | 1.2     | 2750 / 3000 | 72    | Double Centrifugal | -20 to +250     | 3U                  | 5.25   | HB3UFILTER    |
| HB4500A  | 405 / 465      | 2.5     | 2750 / 3300 | 76    | Double Centrifugal | -20 to +250     | 4U                  | 7.00   | HB4UFILTER    |

Data subject to change without notice